

# ALTAFLUOR® DUAL CONTAINMENT TUBING UHP PFA

The CLEAR CHOICE for semiconductor, pharmaceutical, and other critical chemical systems

ALTAFLUOR® DC SERIES DUAL CONTAINMENT TUBING provides end users with an integrated fluid flow solution for critical processes where high purity and safety are primary concerns.

The inner tube, produced exclusively from 100% Virgin Daikin AP231SH UHP PFA resin, ensures the greatest overall performance in critical and aggressive applications. The outer tube, constructed of 100% Virgin grade FEP not only provides excellent clarity for visual inspection, but offers enhanced protection against product damage or personal injury from possible leaks that may occur during the chemical delivery process. The Tube-in-Tube design does not introduce contaminants during the installation process and the ability to provide ALTAFLUOR® Dual Containment Tubing in long continuous lengths reduces the need for excess connections thereby reducing the overall system cost.

## KEY PROPERTIES

- Exclusive use of Daikin AP-231SH UHP PFA Semi -F57 approved resin
- Produced and packaged in a clean room environment
- Ends capped - custom dual containment end caps
- Excellent chemical resistance - (even with common Fluorosurfactants known to attack lower PFA grades)
- Low permeability
- Extremely low extractable levels: metallic and organic
- Extremely smooth surface finish
- Highest mechanical performance vs other PFA and HP PFA tubing products
- Flex life comparable with PTFE
- Laser marked for complete traceability
- Flame resistant - fluoropolymers meet UL 94 V0

## CUSTOM APPLICATIONS

- Custom laser marking
- Custom packaging: straight lengths, short cut-to-length parts
- Private Labeling
- Additional sizes and material selections available upon request

## ALTAFLUOR® DUAL CONTAINMENT TUBING

PART NUMBER	PRIMARY TUBING	OUTER TUBING	PSI@72F (PRIMARY)	WT/FT (LBS)
DC-0250-0500-0C	5/32 ID x 1/4 OD x .047	3/8 ID x 1/2 OD x .062	355	.11
DC-0375-0750-0C	1/4 ID x 3/8 OD x .062	5/8 ID x 3/4 OD x .062	315	.18
DC-0500-0750-0C	3/8 ID x 1/2 OD x .062	5/8 ID x 3/4 OD x .062	235	.21
DC-0750-1000-0C	5/8 ID x 3/4 OD x .062	7/8 ID x 1 OD x .062	155	.30
DC-1000-1250-0C	7/8 ID x 1 OD x .062	1.10 ID x 1.250 OD x .075	120	.44

PACKAGING: Coils of 100 FT or less are packaged in heavy gauge anti-static bag heat-sealed inside heat-sealed heavy clear polybag.

All ends capped. Longer lengths are provided on clean room compatible plastic reels wrapped in anti-static stretch-wrap.

Note: For certifications see 480 Series UHP PFA section



P: 973-300-3344

F: 973-300-3345

E: sales@altaflo.com

A: 23 Wilson Drive, Sparta, NJ 07871

ALTAFLUOR® is a registered trademark of Altaflo LLC

TEFLON™ is a brand of Chemours

NEOFLON® is a registered trademark of Daikin

KYNAR® and KYNAR FLEX® are registered trademarks of Arkema Inc.